THE ENTIRE SYSTEM

Filters:
Holder (595-30-006)
Polariser (595-30-013)
Focusing lens 20 (595-30-007)
Focusing lens 26 (595-30-056)
Colour filters:
blue (595-30-008)
green (595-30-009)
yellow (595-30-010)
red (595-30-011)

Stand:
Clamp mounting
(595-30-005)
Adjustable stand 2 x M6
(595-30-029)
Base plate
(619-30-007)

Accessories/adapters for ring light Ø 66 mm:

Polarising filter set
(595-20-166)

Objective adapters for ring light Ø 66 mm:
66/50 (598-30-017)
66/58 (595-32-258)
66/60 (598-32-043)
66/62 (598-32-127)
M48 x 0,75 (598-32-049)
M55 x 0,75 (598-32-050)

Adapter for
dark field ring light
h = 40 mm
(595-30-083)

Optical element[1]

Goose-neck light
guide, 2-armed
(for no. see list)[2]

Goose-neck combi
light guide, 2-armed
(for no. see list)[3]

Flexible light guide,
1-armed
(for no. see list)[4]

Flexible light guide,
2-armed
(for no. see list)[4]

Back light
(595-30-075)

Line converter attachment
(595-20-140)

Ring lights:
Ø 40 mm, active Ø 7 mm
L = 1000 mm
(598-20-103)

RL Standard Ø 66 mm,
active Ø 9 mm, with
focusing attachment[1]
L = 750 mm
(595-20-005)
L = 1000 mm
(595-20-006)
RL 6-point
Ø 66 mm, active Ø 7,6 mm
with focusing attachment[1]
L = 750 mm
(595-20-001)

Dark field ring light
Ø 66 mm, active Ø 7 mm
L = 1000 mm
(595-20-143)

Mounting adapters for 2-armed combi light guides:
for C-PS and SZ2 stands (619-20-048)
for round column stands
Ø 35/32/30/25 mm (619-20-049)
for S stand (619-20-050)

Interface RS-232
(593-30-008)

F1 (10030)
F1R (10036)

Weighted
insertable module
(633-30-003)

Adapters for Schott
light guides, loss-free:
with collet
(593-30-007)
with clamping screw
(598-30-037)

[1] *included in standard scope of delivery*

[2] *Goose-neck light guide:*
2-armed active Ø 2 x 4.5 mm L = 550 mm (595-20-167)
2-armed ESD active Ø 2 x 4.5 mm L = 550 mm (595-20-168)

[3] *Goose-neck combi light guide:*
2-armed active Ø 2 x 4.5 mm
L = 550 mm, Lflex = 750 mm (595-20-169)

[4] *Flexible light guide:*
1-armed active Ø 5 mm L = 1000 mm (595-20-030)
1-armed active Ø 8 mm L = 1000 mm (595-20-033)
2-armed active Ø 2 x 3 mm L = 1000 mm (595-20-055)
2-armed active Ø 2 x 5 mm L = 1000 mm (595-20-036)
2-armed active Ø 2 x 8 mm L = 1000 mm (595-20-039)

Subject to change without notice. 03/14

PHOTONIC OPTICS

Distributed in Europe by World Precision Instruments | www.wpi-europe.com
UK Office | +44 1462 424700 | wpiuk@wpi-europe.com
German Office | +49 6031 67708-0 | wpide@wpi-europe.com

WORLD PRECISION INSTRUMENTS